

Capacity Range: 125-10000 cfm (3.5-283.2 m3/min)Filtration Grades: High efficiencyPressure Drop: 0.5 psig (0.03 barg)Maximum Operating Pressure: 150 psig (10.3 barg)Maximum Operating Temperature: 125°F (52°C)Minimum Operating Temperature: 34°F (1°C)Element Life: 10 years

Features

- Efficient Equipment Protection: High-efficiency particulate filtration to 0.5 ppm, > 3 microns at 100%, between 0.1 to 3 microns at 99.98%
- Lower Energy Use: Low pressure drop design saves on energy costs and provides an economical drying solution for your compressed air needs
- Extend Equipment Life: High-quality, maintenance-free filters extend element life up to 15 years
- Maximize Uptime: Reduces the effects of catastrophic air/oil separator failures
- Effective Operation: Works on all common mineral and synthetic lubricants



Model Specifications

Model	Flow Rate m3/min (scfm)	Connection Size in	Drain Port in	Weight kg (lb)
F210NG	125	2" MPT	1" FPT	455 (1003)
F430NG	250	2" MPT	1" FPT	455 (1003)
F850NG	500	3" MPT	1" FPT	520 (1146)
F1360NG	800	3" MPT	1" FPT	530 (1168)
F1870NG	1100	3" MPT	1" FPT	660 (1455)
F2550NG	1500	4" FLG	1" FPT	775 (1709)
F3220NG	1900	4" FLG	1" FPT	1225 (2700)
F4070NG	2400	4" FLG	1" FPT	1245 (2745)
F5100NG	3000	4" FLG	1" FPT	1385 (3053)
F7600NG	4500	6" FLG	1 1/2" FLG	1770 (3902)
F10200NG	6000	8" FLG	2" FLG	2460 (5423)
F13600NG	8000	8" FLG	2" FLG	2850 (6283)
F17000NG	10000	10" FLG	2" FLG	4500 (9920)



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.