



Pneumatic No-Loss Drains (PNLD II)

The PNLD II line of fully pneumatic no-loss drains offers a single solution that easily removes condensate with high levels of rust and oil, while eliminating air loss, even at elevated pressure.

Features

The Efficient Choice for Commercial and Industrial Applications The PNLD II requires no electricity, pre-settings or manual intervention, making it ideal for use in commercial and industrial applications. Designed to work with a variety of system components including compressors, receiver tanks, in-line filters, water separators, dryers and coolers, the PNLD II is easy to install and operates virtually clog-free.

Superior Materials, Rugged Construction To ensure maximum service life and compatibility, the PNLD II features a stainless steel float and air cylinder that accommodate higher operating pressures and resist deterioration from corrosion. The drain valves use Viton® seals to prevent deterioration from lubricant carryover in the condensate.

Robust Valve Design The PNLD II features a unique air valve design that uses magnetic force to ensure a positive opening and closing to prevent metal particulate from clogging the drain. An innovative ball valve support and positioning system impedes side loading, which can cause premature sealing failure around the valve stem. A rifle-drilled discharge port ensures that scale and rust exits through the full-port ball valve.



PNLD II Features

- Fully pneumatic drain that requires no electricity
- Handles high volume compressed air systems up to 30,000 cfm (850 m³/min)
- Extended maximum operating pressure up to 750 psi
- Multiple ¾" inlet orifices for ease of installation
- Clear cylinder allows for easy visual inspection of operation
- Maximum liquid temperature of 180°F (82°C) expands operating range
- Stainless steel float prevents deterioration and corrosion
- Full-port ball valve reduces clogging
- Clear body design for easy cycling verification

PNLD II Features

- Fully pneumatic drain that requires no electricity
- Handles high volume compressed air systems up to 30,000 cfm (850 m³/min)
- Extended maximum operating pressure up to 750 psi
- Multiple ¾" inlet orifices for ease of installation
- Clear cylinder allows for easy visual inspection of operation
- Maximum liquid temperature of 180°F (82°C) expands operating range
- Stainless steel float prevents deterioration and corrosion
- Full-port ball valve reduces clogging
- Clear body design for easy cycling verification

Model Specifications

Standard Part Number	Stainless Part Number	Model	Max. Air Flow (cfm)	Max. Operating Pressure (psi)	Control Airpsi
Part # 38439840	N/A	PNLD II 12	400	200	None
Part # 22890214	Part # 47575750001	PNLD II 28 LP	30000	450	40-130
Part # 22699706	Part # 47575751001	PNLD II 28 MP	30000	450	55-130
Part # 22758643	Part # 47575755001	PNLD II 28 HP	30000	750	55-130



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.