

Ultra 4K is an engineered synthetic coolant formulated to provide optimum reliability for rotary screw air compressors. Ultra 4Ks unique formulation helps extend your compressor life and increases total system efficiency versus non-Ingersoll Rand coolants. With a recommended 4,000 hours of service between change-out under normal operating conditions, it helps align your lubricant to your operating needs.

Features

- With up to 4,000 hours of run time, this synthetic lubricant aligns to your operating needs
- Non-foaming performance reduces carryover to improve efficiency and minimize lubricant contamination in your system
- Higher thermal conductivity than poly-alpha-olefins (PAOs) and mineral oils provides consistent viscosity even in a high-temperature environment
- Protects against varnish and deposits to provide wear protection to your trusted equipment
- High flash point of 248°C (478°F) enhances operational safety
- Pour point of -39°C (-38°F) is safe for all weather



Model Specifications

Bottle Size	Part #	Viscosity Index	ISO Viscosity Grade	Run Hours	Base Stock
5 Liter Bottle	47703841	120	46	4000	Synthetic
20 Liter Pail	47696743	120	46	4000	Synthetic



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit www.ingersollrand.com.